

PE/HDPE ROPES

SIZE : 2 mm to 32 mm in 3 strands (3 Ply) & 4 Stands (4 Ply)

COLOUR : Yellow, Blue, Green, Orange, Red, White, Brown and

other colours as per customer requirements

TWIST : Single and double twisting both are available

TOLERANCE: 2 MM to 32 MM = +/-7%

AVAILABLE IN:

- 3 Strand Rope
- 4 Strand Rope
- S Twister Rope
- Z Twister Rope

CHARACTERISTICS:

- Minimal Water Absorption
- Controlled Elongation
- Light Weight
- Smooth Finish

- Floats on Water
- Easy Handling
- Inert to Chemicals
- Heigh Strength

COIL LENGTH AVAILABLE:

- 5 yards to 500 yards.
- Various lengths and packing also available as per buyer requirement.

DIAMETER		CIRC.	WEIGHT		LINEAD DENOITY		AUN TENOU E	
			183M	600'	- LINEAR DENSITY		MIN TENSILE	
ММ	Inch	Inches	(kgs)	(lbs)	Kgs/100m	Lbs/100'	Kgs.	Lbs.
6	1/4"	3/4"	3.36	7.41	1.84	1.24	204	449
8	5/16"	1"	5.78	12.73	3.16	2.12	610	1,344
9	3/8"	1-1/8"	7.46	16.44	4.08	2.74	770	1,696
11	7/16"	1-1/4"	9.51	20.95	5.2	3.49	930	2,048
12	1/2"	1-1/2"	13.17	29	7.2	4.83	1,240	2,731
14	9/16"	1-3/4"	17.56	38.67	9.6	6.45	1,410	3,106
16	5/8"	2	23.41	51.56	12.8	8.59	2,080	4,581
18	3/4"	2-1/4"	29.26	64.45	16	10.74	2,540	5,595
22	7/8"	2-3/4"	43.89	96.68	24	16.11	3,100	6,828
24	1"	3	51.94	114.4	28.4	19.07	4,310	9,493
28	1-1/8"	3-1/2"	70.96	156.29	38.8	26.05	5,830	12,841
32	1-5/16"	4	92.9	204.63	50.8	34.11	7,620	16,784

MAJOR USAGE:

- Fishing
- Industrial use
- Shipping
- Domestic Purpose
- Construction
- Seafaring

