



PP FIBRILLATED ROPE

Decoraoverseas Yellow three strand film rope is a strong, lightweight polypropylene rope that floats and has excellent resistance to oil, marine growth and most common chemicals. Lacks the abrasion resistance of standard monofilament polypro designed to not rot or deteriorate. Also available coil and wooden / plastic reel packing.

CHARACTERISTICS :

- Chemical resistance
- Strong and Durable
- Nowarater absorption
- Unaffecated by weather
- Excellent strength

COLOR

Cost effective & high strength

ROPE RANGE : 2 mm to 32 mm

TWIST RANGE : Single and double twisting

TOLERANCE : 2 mm to 24 mm = +/-5% COIL LENGTHS : 110 Mtr., 500 Mtr. and various

both are available

lengths are available as per buyer requirement.

: Yellow, white and other colors as per customer requirement.

MAJOR USE :

- Fishing
- Shipping
- Construction
- Sports net making
- For Truck use
- Industrial use

- Domestic purpose
- seafaring
- Posrts & ship building yards

DIAMETER		CIR	WEIGHT					
			600'	183M	LINEAR DENSITY		MIN TENSILE	
Inch	ММ	Inches	LBS	KGS	Lbs/100'	Kgs/100m	Lbs.	Kgs
3/16"	5	5/8"	3.60	1.63	0.60	0.89	808	36
1/4"	6	3/4"	6.00	2.72	1.00	1.49	1.249	56
5/16"	8	1"	9.00	4.09	1.50	2.23	1,899	863
3/8"	9	1-1/8"	13.50	6.13	2.25	3.35	2,698	1,22
7/16"	11	1-1/4"	20.00	9.08	3.33	4.96	3,498	1,58
1/2"	12	1-1/2°	24.00	10.90	4.00	5.95	4,196	1,90
9/16ª	14	1-3/4"	36.62	16.63	6.10	9.09	5,066	2,30
5/8"	16	2"	38.40	17.43	6.40	9.53	6,194	2,8
3/4"	18	2-1/4"	54.00	24.52	9.00	13.40	8,491	3,85
7/8"	22	2-3/4"	76.50	34.73	12.75	18.98	11,489	5,21
1"	24	3"	90.00	40.86	15.00	22.33	13,987	6,35
1-1/8"	28	3-1/2*	116.00	52.66	19.33	28.78	18,282	8,30
1-1/4"	30	3-3/4*	138.00	62.65	23.00	34.24	20,982	9,52

STANDARD & TWIST

- 3rd standard (3 Ply)
- Z TwistRope

